


Aluminium column SAL-4,5/B60 dz

diameter 114 mm at ground level



Technical data

Aluminium Column	SAL-4,5/B60 dz
Product code	42107
Column height H [m]	4,5
Wall thickness [mm]	3,0
Net weight [kg]	14,4
Volume [m ³]	0,033
Post top column	luminaires with $\varnothing 60$ spigot entry with weight and windage not exceeding data in resistance calculations
Compatible extension arms	according to resistance calculations
Rooted section h [m]	0,8

Resistance calculations

SAL-4,5/B60 dz code 42107		acceptable windage of single luminaire [m ²] for C _x =0,7			
		Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
extension arm type	acceptable weight of single luminaire	I zone, II location category	I and III zone, II location category to 450 m AMSL	II zone, II location category	III zone, II location category to 755 m AMSL
WA-01	10	0,40	0,31	0,19	0,16
WA-1	10	0,42	0,33	0,21	0,18
WA-2	10	0,28	0,21	x	x
WA-4	10	0,20	0,13	x	x
WA-8/1	10	0,18	x	x	x
WA-11/1	10	0,15	x	x	x
WA-14/1	10	0,18	x	x	x

SAL-4,5/B60 dz code 42107		acceptable windage of luminaires and extension arms [m ²] for C _x =1			
		Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
acceptable mass of luminaires and extension arms [kg]		I zone, II location category	I and III zone, II location category to 450 m AMSL	II zone, II location category	III zone, II location category to 755 m AMSL
20		0,37	0,31	0,22	0,2

- surface: polished aluminium
- anodising in 10 colours, each with possibility of brightening
- option of powder painting in RAL colours (other colours available on request)
- elastomer protection in the color of the column to a height of 350 mm (other height on request)
- ROSA standard wiring chamber
- packing: sleeve material
- passive safety certificate 100NE2