



### Technical data

Column	SAL DECO-1 LED
Code	42928
Electrical class	II
Ingress protection	IP65
LEDs type	CREE MK
Correlated colour temperature [K]	5 000
LEDs power [W]	65
LEDs quantity	8
Nominal input voltage [V]	120-277 AC
Frequency [Hz]	50/60
Power consumption [W]	73
Luminous flux * [lm]	3 400
Supply current [mA]	700
Height [mm]	4 350
Diameter at the base plate [mm]	132
Setup	electrical equipment built on top and closed with heat-resistant glass; cap with an external louvre in the form of convex mirror squares; 3 connecting arms with a circular roof
Weight [kg]	43,5
Volume [m <sup>3</sup> ]	0,35
Foundation / reinforcing cage	B-51A / Z-51A
Foundation code/ reinforcing cage code	311151A / 311251A
Hot galvanized nut set	4008

- Low Voltage Directive LVD 2006/95/WE, norm PN-EN 60598-1
- Directive EMC 2004/108/WE, norms: PN-EN 55015, PN-EN 61547, PN-EN 61000-3-2, PN-EN 61000-3-3

- surface: polished aluminium
- anodizing in 10 colours each with possibility of brightening
- option of powder painting in RAL colours (other colours available on request)
- elastomer protection option in the color of the column to a height of 350 mm (other height on request)
- ROSA standard wiring chamber
- packing: sleeve material / carton / foil

\* including LEDs tolerance parameter accuracy +/- 3%